

PRODUCT CARD

Manufacturer: Lanberg
Z20314

19" FREE-STANDING RACK 37U/600X600 DEMOUNTED FLAT PACK BLACK LANBERG

Catalog nr: FF01-6637-12B



Product description

One section freestanding cabinet Lanberg FF01-6637-12B is a solution designed to expand networks, installation of cabling and equipment in size 19" with max. 800kg. loading capacity. It can be used in networks, server rooms, small, medium businesses and data centers which needs lot of space in cabinet for network equipments. It can also work in low voltage systems such as cable television networks, alarm systems, fire protection systems and access control systems, CCTV and IP surveillance. Construction is made of high grade cold rolled steel which characterised by excellent design and high quality of craftsmanship. The cabinet allows full adjustment of the depth of the vertical mounting rails. It is equipped with front temper glass door with lock and possibility installing on right or left side. It has removable side panels (include locks) and rear solid steel door with lock. You can put the wiring through entry cable on top and bottom panels (with blank entry panels). The fan tray include 2 fans 230V. In addition, parcel includes additional accessories for rails mounts, M6 cage nuts and blank entry panels. Cabinet structure for self-assembly is in three flat packs which facilitates transport.

Features:

- Manufacturer: Lanberg,
- Manufacturer code: FF01-6637-12B,
- Cabinet type: Freestanding,
- Body color: Black RAL9004,
- Height: 37U,
- Cabinet dimensions (W x D x H): 600x600x1833 mm,
- Packaging dimensions (W x D x H): Top & Bottom - 63x169x10 cm, Doors - 62x63x13 cm, Frame - 61x174x25 cm,
- Floor panel: 4 castors with brake + adjustable legs,
- Loading capacity: Do 800 KG,
- Degree of protection: IP20,
- Top with fan tray: 2 fans 230V in top cover,
- Doors type: Front - Temper glass, Rear - Steel,
- Standard: ANSI/EIA RS-310D, IEC297-2, DIN41494; PART1 & PART7, ETSI,
- Material: High grade cold rolled steel, powder coated,
- Thickness: Mounting profile - 2,00mm, Others - 1,2mm - 1,5mm,
- Cable entry panel: Top, Bottom (adjustable),
- Included: Accessory bag, locks for front and rear doors and two side panels, 20 cage nuts M6.

Additional accessories:

- AK-1002-B – Lanberg fixed shelf for freestanding Lanberg cabinet
- AK-1004-B – Lanberg front and back fixed shelf for wall mount and freestanding Lanberg cabinet
- AK-1006-B – Lanberg sliding shelf for freestanding Lanberg cabinet
- AK-1008-B – Lanberg support board for wall-mount and free-standing Lanberg cabinet
- AK-1101-B – Lanberg brush panel 1U
- AK-1201-B – Lanberg cable management type A
- AK-1202-B – Lanberg cable management type B
- AK-1302-S – Lanberg 50 cage nuts M6
- AK-1401-B – Lanberg blank panel 1U
- AK-1402-B – Lanberg blank panel 2U

Product features

Width [mm]	600,00
Height [mm]	1 833,00
Type of cabinet	Stagnant; One-section; Self-assembly
Height [U]	37,00
Depth [mm]	600,00
Maximale Belastung [kg]	800,00
Weatherproof rating IP	20,00
Profile sheet thickness [mm]	2,00
Other elements sheet thickness [mm]	1,50
Front door types	Glass
Rear door type	Metal
Included Accessories	Front lock; Rear lock; Side locks; Ventilation panel (2 fan); M6 screws
Weight [kg]	18,00

Logistics data

EAN	
VAT rate [%]	23,00 %
Guarantee	24
Country of origin	CN