

SC-Series LED-backlit Display 27" | 24" | 22" | 19"



The SC-Series surveillance displays designed for 24/7 operation feature Anti-Burn-in™ technology which prevents image retention while performing nonstop in security and surveillance environments. The series also includes enhanced image quality and settings control such as gamma curve selection, black-level adjustment, and CCTV mode that help create richer images even under unfavourable lighting conditions coming from low light surveillance footage.

















Others







AG Neovo SC-Series

Industry-leading Reliability

The SC-Series is specially designed to transcend the challenge of enduring 24/7 operations. AG Neovo's Anti-Burn-inTM technology also prevents image ghosting while performing continuous mission-critical operations.

Enhanced Image Clarity

Displays with exceptionally clear images with cutting-edge gamma curve selection, black-level adjustability, and high dynamic contrast ratio 20,000,000:1; the SC-Series can capture darker details and deliver premium images, thereby enhancing image detail quality. A pre-configured CCTV mode has been geared specifically for surveillance control rooms to adjust the display's video settings such as sharpness, colour temperature, and brightness to maximise image clarity especially in low light surveillance footage at night.





Others

AG Neovo SC-Series



Adaptable to Your Environment Needs

With adaptability in mind, the SC-Series provides an array of configurations designed to help you tailor the display to your surveillance needs. This includes on/off toggles for the blue screen or the power LED and selectable aspect ratios including 16:9, 4:3, 1:1 or even a custom zoom mode which helps accommodate the display to the conditions of your control room regardless of the input signal.

Features

- \bullet Full HD 1920 x 1080 resolution
- Crisp 20,000,000 dynamic contrast ratio
- 3-sided narrow bezel design for seamless multi-display setups (27" and 24" only)
- Image Enhancer: 3D Comb Filter / Deinterlace / Noise Reduction / Image Rotation / Freeze
- Adjustable image settings via analogue inputs
- Versatile inputs: HDMI, VGA, Composite (BNC)
- BNC passive loop-through output port
- Flicker-free display technology reduces eye discomfort

- Quick signal-switching time
- \bullet Black-level adjustment for presenting more details in dark images
- CCTV picture mode for maximum image detail and clarity in low light footage
- Colour engine enhance for colour saturation
- Selectable aspect ratios: 16:9, 4:3, 1:1 or custom zoom
- Built-in speakers and audio mini-jack in/out connection
- VESA mount compatibility for flexible installation
- Designed and developed for continuous 24/7 operation













Specification	ns	SC-27E	SC-24E	SC-22E	SC-19E
Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time Surface Treatment	LED-Backlit TFT LCD (VA Technology) 27.0" FHD 1920 x 1080 0.311 mm 300 cd/m² 20,000,000:1 (DCR) 178°/178° 16.7M 5 ms Anti-Glare Treatment (Haze 25%), 3H Hard Coating	LED-Backlit TFT LCD (IPS Technology) 23.8" FHD 1920 x 1080 0.275 mm 250 cd/m² 20,000,000:1 (DCR) 178°/178° 16.7M 5 ms Anti-Glare Treatment (Haze 25%), 3H Hard Coating	LED-Backlit TFT LCD (TN Technology) 21.5" FHD 1920 x 1080 0.248 mm 250 cd/m² 20,000,000:1 (DCR) 170°/160° 16.7M 3 ms Anti-Glare Treatment (Haze 25%), 3H Hard Coating	LED-Backlit TFT LCD (TN Technology) 18.5" 1366 x 768 0.300 mm 250 cd/m² 20,000,000:1 (DCR) 170°/160° 16.7M 3 ms Anti-Glare Treatment (H 25%), 3H Hard Coating
Frequency (H/V)	H Freq. V Freq.	24 kHz-83 kHz 50 Hz-75 Hz	24 kHz-83 kHz 50 Hz-75 Hz	24 kHz-83 kHz 50 Hz-75 Hz	24 kHz-83 kHz 50 Hz-75 Hz
Input	HDMI VGA Composite	1.4 x 1 15-Pin D-Sub x 1 BNC x 1	1.4 x 1 15-Pin D-Sub x 1 BNC x 1	1.4 x 1 15-Pin D-Sub x 1 BNC x 1	1.4 x 1 15-Pin D-Sub x 1 BNC x 1
Output	Composite	BNC x 1	BNC x 1	BNC x 1	BNC x 1
Other Connectivity	USB	2.0 x 1 (Service Port)	2.0 x 1 (Service Port)	2.0 x 1 (Service Port)	2.0 x 1 (Service Port)
Audio	Audio In Audio Out Internal Speakers	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (3.5 mm) 2W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (3.5 mm) 2W x 2	Stereo Audio Jack (3.5 mm) Stereo Audio Jack (3.5 mm) 2W x 2	Stereo Audio Jack (3.5 m Stereo Audio Jack (3.5 m 2W x 2
Power	Power Supply Power Requirements On Mode Stand-by Mode Off Mode	Internal AC 100-240V, 50/60 Hz 23W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 22W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 21W (On) < 0.5W < 0.5W	Internal AC 100-240V, 50/60 Hz 16W (On) < 0.5W < 0.5W
Operating Conditions	Temperature Humidity	0°C-40°C (32°F-104°F) 10%-90% (non-condensing)	0°C-40°C (32°F-104°F) 10%-80% (non-condensing)	0°C-40°C (32°F-104°F) 10%-80% (non-condensing)	0°C-40°C (32°F-104°F) 10%-80% (non-condensi
Storage Conditions	Temperature Humidity	-20°C-60°C (-4°F-140°F) 5%-90% (non-condensing)	-20°C-55°C (-4°F-131°F) 5%-93% (non-condensing)	-20°C-55°C (-4°F-131°F) 5%-93% (non-condensing)	-20°C-55°C (-4°F-131°F) 5%-93% (non-condensin
Mounting	VESA FPMPMI	Yes (100 x 100 mm)	Yes (100 x 100 mm)	Yes (100 x 100 mm)	Yes (100 x 100 mm)
Stand	Tilt	-5° to 23°	-5° to 23°	-5° to 23°	-5° to 23°
Security	Kensington Security Slot	Yes	Yes	Yes	Yes
Dimensions	w/Base (W x H x D) Packaging (W x H x D)	611.9 x 454.7 x 238.7 mm (24.1" x 17.9" x 9.4") 704.0 x 460.0 x 140.0 mm (27.7" x 18.1" x 5.5")	540.6 x 396.1 x 194.0 mm (21.3" x 15.6" x 7.6") 620.0 x 420.0 x 122.0 mm (24.4" x 16.5"x 4.8")	505.2 x 380.8 x 194.0 mm (19.9" x 15.0" x 7.6") 557.0 x 387.0 x 117.0 mm (21.9" x 15.2" x 4.6")	441.9 x 356.2 x 194.0 mm (17.4" x 14.0" x 7.6") 492.0 x 360.0 x 123.0 mm (19.4" x 14.2" x 4.8")
Weight	w/Base Packaging	5.3 kg (11.7 lb) 7.3 kg (16.1 lb)	3.8 kg (8.2 lb) 5.4 kg (11.9 lb)	2.8 kg (6.2 lb) 4.2 kg (9.3 lb)	2.3 kg (5.1 lb) 3.6 kg (7.9 lb)
Regulation Approval	Certifications & Compliance	FCC, CE, CB, WEEE, RoHS, REACH, EAC	FCC, CE, CB, WEEE, RoHS, REACH, EAC, BSMI	FCC, CE, CB, WEEE, RoHS, REACH	FCC, CE, CB, WEEE, RoH REACH, EAC
Accessories	Supplied	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Start Guide, Warranty Card	Power Cord, VGA Cable, Audio Cable, Quick Star Guide, Warranty Card
Optional Accessories		Wall Mount: PMK-01 Desk Mount: DMC-01 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-01, WMK-03	Wall Mount: PMK-01 Desk Mounts: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02 Ceiling Mount (Landscape only): CMP-01 + WMK-03 Wall Mounts (Landscape only): WMA-01, WMK-03





Global Headquarters

Taipei, Taiwan

EMEA Regional Headquarters

Capelle a/d Ijssel, The Netherlands

North & South America Regional Headquarters

San Jose, CA, U.S.A.

Asia-Pacific Regional Headquarters

Taipei, Taiwan

Canada Sales Office

Vancouver, B.C., Canada

China Sales Office

Shanghai, China

Czech Republic Sales Office

Brno, Czech Republic

Denmark Sales Office

Støvring, Denmark

Germany Sales Office

Mechernich, Germany

Italy Sales Office

Livorno, Italy

Poland Sales Office

Warsaw, Poland

Spain Sales Office

Barcelona, Spain

Ukraine Sales Office

Lviv, Ukraine

displays.agneovo.com

